

BETOTEX

CONCRETE CURING AGENT ON SYNTHETIC
RESIN BASIS



Product description

BETOTEX is milky white liquid, membrane-forming sealer for curing and sealing newly placed concrete floors and screeds. BETOTEX creates a clear, uniform moisture-retentive film. Curing with BETOTEX is specially relevant under conditions of high temperatures, low atmospheric humidity and in areas where there is strong air draught.

Properties

- cost effective
- creates uniform transparent film, which prevents too rapid drying out process
- reduces plastic shrinkage cracks occur
- easy to apply
- improve of strength properties of near surface layer
- could be used inside and outside conditions

Uses

- horizontal and vertical concrete surfaces
- industrial floors
- concrete screeds
- elevated floors, rafts, columns, walls, etc
- parking decks
- concrete roads, pavements

Technical specifications

| | |
|-------------------------|------------------------|
| aspect: | milky white liquid |
| density: | 1,10 g/cm ³ |
| PH: | 11 ± 0.1 |
| processing temperature: | > 5 °C |
| surface temperature : | > 5 °C |
| soluble: | in water |
| non-flammable | |

Consumtion

0,08 – 0,15 l/m²

Consumption is approximate and depends on the porosity of the surface.

Processing

BETOTEX is ready to use product. Surfaces must be clean and free of all loose dirt, oil, water puddles and other curing products. Application can be sprayed or flushed, distributed evenly with brush or rubber squeegee.

Similar to paint spraying process, care should be taken not to spray too much BETOTEX in one place to avoid unfavorable optional appearance. Standard spraying equipment with suitable nozzles is fit for applying BETOTEX. All equipment should be cleaned carefully with water after use.

Packaging

25 litre pails.
1000 litre containers

Health and safety

No hazardous substance according to the hazardous substances regulations, no hazardous good according to the transportation regulations for hazardous goods.

Contact with skin and eyes to be avoided. Direct contact may result in mild irritation.

Storage

Well closed, frost-free, protected from sun radiation and contamination. Self life at least 1 year, if correctly stored.

Sales

Betotrade OÜ
Tapri 13, Tallinn, Harjumaa, 11415
Tel: +372 656 6767
E-mail: info@betotrade.ee